

**HOLLAND & KNIGHT LLP**

**701 Brickell Avenue  
Suite 3000  
Miami, Florida 33131  
(305) 789-7773**

**Application  
for  
United States  
Letters Patent**

filed on behalf of

Applicant(s): Manish Gupta, Jose E. Moreira  
Adam J. Oliner and Ramendra  
K. Sahoo

For: Hybrid Method for Event Prediction  
and System Control

Attorney Docket: YOR920030242US1

# 1396014\_v1

HYBRID METHOD FOR EVENT PREDICTION AND SYSTEM CONTROL

5 CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] Not Applicable.

STATEMENT REGARDING FEDERALLY SPONSORED-RESEARCH OR  
DEVELOPMENT

10 [0002] Not Applicable.

INCORPORATION BY REFERENCE OF MATERIAL SUBMITTED ON A  
COMPACT DISC

[0003] Not Applicable.

15

FIELD OF THE INVENTION

[0004] The present invention is generally directed towards a control  
system for a computer cluster. More particularly, the present invention is  
directed toward a hybrid method and apparatus for predicting the system  
20 performance of, and the occurrence of critical events in, a computer cluster  
formed from a series of nodes.

BACKGROUND OF THE INVENTION

[0005] Networks or clusters of computers are used for all types of  
25 applications in the modern world. In order for these clusters of computers to  
function efficiently and effectively, it is important that the individual computers

that make up the cluster function properly. If any individual computer in the cluster unexpectedly fails, the effect on the cluster can be catastrophic and cascading. Once an error in the cluster has been detected, it is often possible to take corrective measures to minimize the harm to the overall functioning of the cluster. However, given the speed of modern business and the importance of certain computer clusters, even small amounts of down time can prove extremely costly. Therefore, it would be very advantageous to be able to predict errors or system failures and take corrective action prior to their occurrence.

10

[0006] Several techniques have been previously proposed in the literature for using proactive system management to improve the performance of computer clusters. Some of these techniques have included attempts to predict the occurrence of failures and the use of software rejuvenation. Successful prediction of errors in a computer system in particular offers the promise of enabling significantly improved system management. However, prior techniques for predicting errors have been unreliable and have had several other deficiencies that have prevented them from being widely accepted. Therefore, what is needed is an improved method of predicting the occurrence or errors in a computer cluster and transforming the system to minimize the impact of the predicted errors.

15

20

#### SUMMARY OF THE INVENTION

[0007] A preferred application of the present invention is directed toward a method of predicting the occurrence of critical events in a computer cluster having a series of nodes. In accordance with the method, an event log

25

that contains information concerning critical events that have occurred in the computer cluster is maintained. A system parameter log that contains information concerning system status for each node in the cluster is also maintained. The system parameter log preferably includes at least few  
5 environmental parameters like node temperature, a utilization parameter of a central processing unit of a node in the cluster and a corresponding time value. The event log and the system parameter log are filtered such that some redundant critical event information and system parameter information is not maintained in the event log and the system parameter log. A Bayesian  
10 network model that represents the computer cluster and the nodes is developed based upon the information in the event log and the system parameter log. In accordance with the Bayesian Network, a time-series mathematical model is used to predict future values of the system parameters. A rule based classification system is then used to predict the occurrence future  
15 critical events. A warning window is formed for each node in the cluster such that the warning window contains a predicted performance parameter or critical event occurrence for the node for a predetermined future period of time. Thus, the future performance of a node in the cluster is predicted based upon the information in the event log and the system parameter log.  
20 [0008] Another application of the present invention is directed towards a method of improving the performance of a computer cluster having a series of nodes. In accordance with the method, the occurrence of critical events in the nodes in the computer cluster is monitored. The system performance parameters of the nodes in the computer cluster are also monitored.  
25 Information concerning the critical events and the system performance parameters is saved in a database. The system performance parameters

concern at least one of the node temperature, processor utilization value, network bandwidth and available memory space. The saved information is filtered to remove information that is not determined to be useful in predicting the future performance of the nodes. A time-series mathematical model is applied to the system performance parameters to predict future values of the system performance parameters. The time series mathematical model is preferably one of an auto regression, a moving average and an autoregressive moving average model. Rule based classifications are used to associate some of the system performance parameters with the occurrence of the critical events. A node representation is created for each node in the computer cluster based upon the monitoring and a cluster representation is created based upon the node representations. The node representations are periodically examined to predict future node performance and the cluster representation is used to redistribute tasks among the nodes based upon the predicted node performance. The cluster representation and the node representation form a Bayesian Network that represents relationships between the occurrence of the critical events and the system performance parameters.

[0009] Yet another application of the present invention is directed toward an information processing system that includes a computer cluster having a series of nodes. A control system monitors critical events that occur in the computer cluster and the system parameters of the nodes. A memory stores information related to the occurrence of the critical events and the system parameters of the nodes. A filter removes redundant information from the stored information to reduce storage requirements of the system. A dynamic probe generator determines when to collect additional information concerning the system parameters or the critical event occurrence based upon

the operation of the system. The information processing system has a Bayesian Network model that predicts a future occurrence of a critical event based upon an observed relationship between the system parameters and the occurrence of critical events. The Bayesian Network model includes a time-series modeler for predicting future values of the system parameters and a rule based classification system for associating the system parameters with the occurrences of the critical events.

#### BRIEF DESCRIPTION OF THE DRAWINGS

10 [0010] FIG. 1 is a flowchart of a method in accordance with an embodiment of the present invention;

[0011] FIG. 2 is a high level block diagram showing an information processing system in accordance with another embodiment of the present invention; and

[0012] FIG. 3 is a flow chart illustrating another method in accordance with an embodiment of the present invention.

#### 20 DETAILED DESCRIPTION

[0013] The present invention is directed toward a method and apparatus for predicting error occurrences in a computer cluster that includes a series of nodes. In such a cluster system, prediction of a specific node's failure can be used to steer jobs away from the potentially failing node. This can be done prior to launching a job by avoiding the error prone node when scheduling the job, or after launching a job by migrating the running job to a

healthier node. Such predictions can also help schedule system maintenance at appropriate times to avoid unplanned outages. Even if the prediction of an error happens too late to allow proactive action, the same analysis can serve as a foundation for more effective error isolation (e.g., identifying the node that  
5 led to an error, given an avalanche of errors subsequently observed in a cluster).

[0014] Referring now to FIG.1, a flow chart illustrating an information processing method 100 according to a preferred embodiment of the invention  
10 is shown. The information processing method 100 is based upon the collection of event information and the transformation of the system based upon the collected information as shown in step 102. The collected information concerns critical events 104 that occur in the system and system performance parameters 106 that relate to the conditions under which the  
15 system is operating. More particularly, the system performance parameters 106 relate to system state variables such as temperature, central processing unit utilization, time, processor number, user time, idle time, input/output time, etc. These system state performance parameters 106 relate to the performance of the system and do not typically represent unexpected events.  
20 Thus, the system state parameters 106 are preferably recorded at predetermined intervals of time. The length of the interval depends upon the nature of the parameters 106 being recorded. Conversely, critical events 104 are events that represent failures of the system based on various hardware or software errors or node failures that are typically unexpected and detrimentally  
25 affect the systems performance. Thus, the critical events 104 are preferably recorded when they occur along with the approximate time of occurrence and

the node or location at which they occurred. In addition, the occurrence of a critical 104 can prompt the system to record additional system performance parameters 106 that may have led to the critical event 104.

5 [0015] The critical events 104 and the system performance parameters 106 are fed into a dynamic Bayesian Network Model 108. Bayesian networks are complex diagrams that organize a body of knowledge in any given area by mapping out cause-and-effect relationships among key variables and encoding them with numbers that represent the extent to which one variable is  
10 likely to affect another. The Bayesian Network Model 108 of the embodiment of FIG. 1 uses rule based prediction criteria 110 to predict future critical events 112 that occur when certain conditions are present and time-dependent variable prediction criteria 114 to make predictions 116 concerning time-dependent variables that occur at predictable intervals of time. By combining  
15 these methods of analysis, an improved hybrid prediction system 100 for large clusters of computers is achieved.

[0016] The Dynamic Bayesian Network 108 applies the decision criteria 110 and 114 to the logged information 104 and 106 to predict future critical  
20 events 112 and values for time-dependent variables 116. These predictions 112 and 116 are used to provide valuable information 118 concerning the computer cluster and its nodes' present and future performance. This information 118 includes the nodes and/or events that are causing critical events 104, the type of critical events 104 likely to occur in the future and the  
25 dependency between critical events 104 and system performance parameters 106. This information 118 is then used for event prevention and system



transformation 102. System transformation 102 involves job scheduling and process migration away from troublesome nodes or times. The information 118 can also be used to determine what seemingly benign events occurring in the computer cluster are actually causing subsequent critical error events 104.

5

[0017] The prediction system represented in steps 112 and 116 preferably begins in a tabular state. That is the predictive models 112 and 116 are not built based on any assumptions about the conditions under which errors will occur or the behavior of the independent variables of the cluster.

10 Over time, the system 100 learns the error and event patterns and is able to flag nodes that have a high probability of failing or experiencing the occurrence of a critical event and the times at which any critical events are likely to occur. Thus, the system 100 predicts failures in an adaptive manner that depends upon the past performance of the cluster. This aspect of the

15 invention makes it useful with a wide variety of types of clusters having unknown operating parameters and failure rates.

[0018] Referring now to FIG.2, there is shown a block diagram of an information handling system 200 according to an embodiment of the invention.

20 The system 200 is managed by a control system 202 that preferably comprises a processor, a memory, and an input/output (I/O) subsystem. The control system 202 monitors a physical cluster 204 of computers or nodes that are arranged into a network. The control system 202 gathers information concerning time-dependent properties and system performance properties of

25 the physical cluster 204 as well as the occurrence of any critical events. This information is fed through a filter 206 that aligns the events and eliminates any

redundant events or information. The filter 206 also categorizes the events as time-dependent or time-independent as well as either derived or primary variables and evaluates the information according to a set of evaluation criteria to determine what information needs to be logged as relevant and what information may be discarded as irrelevant. Primary variables represent raw data measurements from the system while derived variables are calculated or computed based upon the primary variables. Time-dependent variables include among other things processor utilization, network bandwidth and computer chip temperature. Examples of time-independent variables include network topology, disk size, number of processors and memory size. The filtered information from the filter 206 is stored in a central measurement database 205. The time-independent filtered information also passes from the filter 206 to a rules based classification routine 208 that develops a set of rules based upon detected relationships between the time-independent information and the occurrence of critical events. These rules associate a number of events that signal a potential critical event with the critical event which they tend to predict. The critical events are assigned a severity value that reflects the relative importance of the critical event with respect to the clusters 204 performance and the associated events are assigned a value that indicates their correlation with a critical event. These rules are used to develop a cluster representation 212 and a node representation 214.

[0019] The time-dependent information is passed to a time series modeling routine 210 that develops mathematical algorithms through the use of linear time-series and/or wavelet techniques that can be used to predict the future values of the time-dependent variables. The time series mathematical

models are preferably an auto regression, a moving average or an autoregressive moving average model. However, it will be readily appreciated by one skilled in the art that a wide variety of mathematical modeling techniques could be used. These algorithms are then used to further improve  
5 the created cluster 212 and node representations 214. While the time-series modeling routine 210 is feeding the cluster representation 212 predicted future states, the cluster representation 212 is making predictions about what errors or other critical events should be expected at some future time and the nodes at which they are expected. The confidence level of these predictions is  
10 inherently present in the cluster representation 212. The node representations 214 which are predicting that a severe error is likely to occur in their associated nodes can be flagged as potential problems. The control system 202 for the cluster 204 is notified so that it may make scheduling and data migration choices appropriately. As a result of the actions of the control  
15 system 202, the system itself will output more information to data filtering mechanism 206, thus feeding the process and completing the cycle.

[0020] For each node in the physical cluster 204, where a node is the smallest set of components for which the system differentiates, a static  
20 Bayesian Network is maintained. This Bayesian Network is referred to as the node representation 214. The set of node representations 214 forms the cluster representation 216. The error or event stream output from the data filter 206 is used as training data for the node in which the event occurred. A node representation 214 is preferably only maintained for those nodes in the  
25 physical cluster 204 in which at least one error has occurred. Since nodes of the system will often be error-free, save for a few problem nodes, only

maintaining node representations 214 for error prone nodes greatly reduces the processing power and memory required to implement the system.

[0021] As previously discussed above, the system 200 preferably reports information falling into two categories. Events constitute the first category of information. These events are generally stored in the form of event logs. The second category of information involves the operating states of the system. This second category includes such information as the variable environmental conditions of a node (e.g. temperature), the amount of utilization of a CPU, the current time, etc. The amount of this information that is reported by a cluster may be enormous. Fortunately, there tends to be a great deal of redundancy in the information. Thus, a script based filtering mechanism such as filter 206 is preferably used to parse this information to make it more easily manageable and decrease the processing and data storage requirements of the system. Such a filter 206 eliminates the redundant information, and associates events with the state of the system at the time of the error. This error/state association information forms a stream of error and event information that is used to monitor the present performance of the system and predicts its future performance. The output information output by the script filtering mechanism 206 is preferably stored in a central database 205.

[0022] Once the cluster representation 212 and the node representations 214 are computed along with the associated probabilities that a critical event will occur at a particular node within a particular time window, a policy for handling the critical event based upon the type of critical event and

the likelihood of its occurrence can be formulated. As will be appreciated by those skilled in the art, the type of critical event predicted to occur will determine the corrective action that will be dictated by the policy. The corrective action may include migrating an ongoing process to a different node or rerouting an upcoming action through a different node or path. In addition, actions may be rescheduled to occur at a time which the cluster 212 and node representations 214 indicate a critical event is less likely to occur.

[0023] If the information gathered through the logging of events and system performance parameters is not sufficient to base a decision upon, a dynamic probe generator 216 will probe the physical cluster 204 for additional information related to the desired properties of the cluster 204. These probes can be directed toward collecting additional information from past records or future sets of events. Thus, the use of a dynamic probe generator 216 further decreases the data storage requirements of the central measurement data base 205.

[0024] Referring now to FIG. 3, a flow chart of a method 300 for predicting the occurrence of critical events in a computer cluster in accordance with an embodiment of the present invention is shown. The method begins in step 302 with the collecting of event information and system performance parameters. The event information preferably concerns the occurrence of critical events that adversely affect the performance of the cluster or one of its nodes and the system performance parameters preferably bear some relationship to the potential occurrence of such a critical event. The method then proceeds to step 304 wherein rule-based algorithms are used to establish

and extract associative rules for predicting the probable occurrence of critical events within a specified time window or time limit and the variables that are likely to indicate the potential occurrence of such an event. In step 306, time-dependent variable algorithms such as linear time-series and wavelets are used to create models that predict future values of the system performance parameters. A static or dynamic Bayesian Network is then created that represents the determined interaction and relationship between the system performance parameters and the occurrence of critical events in step 308. In step 310, the occurrence of future critical events within a specified time-limit is predicted by associating the critical event with other events that tend to precede the critical event. Finally, in step 312, the cluster's performance is modified based upon a predicted occurrence of a critical event.

[0025] What has been shown and discussed is a highly simplified depiction of a programmable computer apparatus. Those skilled in the art will appreciate that other low-level components and connections are required in any practical application of such a computer apparatus. Therefore, while there has been described what is considered to be the preferred embodiment, it will be understood by those skilled in the art that other modifications can be made within the spirit of the invention.

We claim: